



LED Track Light Berlin Slim Datasheet

Number of heads	1
Mounting	Track mounting
Lamps description	LED 15 W, 20 W, 30 W, CRI 90
Luminaire luminous flux	110 lm/W
Voltage (V)	220-240
Environment	Indoor
Notes	LED Track Light Berlin Slim driver is located inside of the thin luminaire adapter. This makes it possible to avoid additional heat when operating the luminaire.

OPTICAL

Reflector finish	Aluminum
Aiming	Adjustable 350° and 90°
Light distribution symmetry	Symmetric
Beam angle	24°, 40°
Color temperature	2700K, 3000K, 3500K, 4000K, 5000K, 6000K

ELECTRICAL


Wattage	15 W, 20 W, 30 W
Transformer mounting	Integral
Transformer type	Electronic
Frequency	50-60 HZ
Voltage	220-240 V

PHYSICAL

Spot diameter (mm)	Ø 70
Construction material	Aluminium, PVC
Weight (kg)	1,0
Luminaire lifespan	50 000h
LED module	BRIDGELUX COB LED
Driver	ALLOOKING, PHILIPS
Working temperature	-30 to +40 °C
Warranty	5 years from purchase date




LED light to be installed on 3-phase
4 wire track.



● White ● Black

Dimensions: Ø70 x 245mm



CERTIFICATIONS

