

RIO CEILING AND WALL MOUNTED LUMINAIRE

PRODUCT DATASHEET
RIO_15W_CCT_LED_1350

Contemporary dome shaped surfaced LED luminaire. Electronic, fixed output control gear. Diffuser : Polycarbonate (PC). IP54. Ceiling or wall mounting. via 2 fixing holes. Complete with 3000 - 4000 - 6000K LED. There is option to change CCT by dip switch.



IP54

IK05

89,34 lm/W

TECHNICAL DATA

SKU:

6004000076

Electrical data

Nominal wattage	15 W
Operating wattage	14,56 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

Photometrical data

Color temperature (CCT)	3000/4000/6000 K
Luminous efficiency	89,34 lm/W
Luminous flux	1358 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

Light technical data

Beam angle	120°
------------	------

Dimensions and weight

Diameter	Ø220 mm
Height	50 mm
Weight Neto	0,462 kg

Materials

Body material	Polycarbonate
Housing color	White
Difuser material	Polycarbonate (PC)

Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

Lifespan

Lifespan L80/B10 at 25°	30000 h
-------------------------	---------

Led Brand	EPISTAR
-----------	---------

Driver	Integrated
--------	------------

Mounting information

Mounting type	Surfaced
Mounting location	Ceiling / Wall


Capabilities	
Dimmable	No
Type of connection	Via 2 fixing holes
Standards and Certificates	
Protection class IK	IK05
Type of protection IP	IP54
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package	
Product code	6004000076
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	225x225x55 mm, 0,552 kg
Product EAN code	4772007009206
Second package	
Package	Carton box
Units in second package	10 pcs
Package diameters, weight bruto	465x305x250 mm ; 5,998 kg
ShipPing carton EAN code	4772007009220

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6004000076 RIO_15W_CCT_LED_1350
6004000077 RIO_18W_CCT_LED_1620
6004000078 RIOSENS_15W_CCT_LED_1350
6004000079 RIOSENS_18W_CCT_LED_1620

