

**ROSA** SQUARE LED PANEL

**PRODUCT DATASHEET**
**ROSA80\_S\_28W\_LED\_2290**

A recessed LED luminaire with a 10mm no frame profile. Electronic, fixed output gear. IP65 environmental degree, IK08. Driver IP20, IK03. Body: aluminum white painted (RAL9016). Diffuser: Polycarbonate, UV-stabilised. Electrical connection via push wire terminal blocks. Complete with 4000K LED.



IP65

IK08

85,24 lm/W

**TECHNICAL DATA**

SKU:

6003000051

## Electrical data

Nominal wattage	28 W
Operating wattage	26,97 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

## Photometrical data

Color temperature (CCT)	4000 K
Luminous efficiency	75,90 lm/W
Luminous flux	2299 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

## Light technical data

Beam angle	120°
------------	------

## Dimensions and weight

Dimension	215x215x24 mm
Weight Neto	0,496 kg
Cut out hole size	Ø195 mm

## Materials

Body material	Aluminum
Housing color	White
Difuser material	Polycarbonate, UV-stabilised.

## Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

## Lifespan

Lifespan L80/B10 at 25°	50000 h
Led Brand	EPISTAR
Driver	LS-30-300RI

## Mounting information

Mounting type	Recessed
Mounting location	Ceiling
Capabilities	
Dimmable	No
Type of connection	Wires 2-pole
Standards and Certificates	
Protection class IK	IK08
Type of protection IP	IP65
Standards	CE, RoHS
Warranty	36 months

## LOGISTICAL DATA

### Main package


Product code	6003000051
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	265x246x30 mm ; 0,598 kg
Product EAN code	4772007007509

### Second package

Package	Carton box
Units in second package	50 pcs
Package diameters, weight bruto	880x505x295 mm ; 31,300 kg
ShipPing carton EAN code	4772007007608

## ACCESSORIES

## ENERGY EFFICIENCY



## ALL FAMILY PRODUCTS

- 6003000048 ROSA80\_S\_8W\_LED\_600
- 6003000049 ROSA80\_S\_14W\_LED\_1200
- 6003000050 ROSA80\_S\_20W\_LED\_1780
- 6003000051 ROSA80\_S\_28W\_LED\_2290



TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.