PRODUCT DATASHEET BRENTSENS_50W_LED_5500

Brent LED floodlight has new innovative design. Protection class IP65. Impact resistance IK08. Housing aluminum (AS90), coated with grey (RAL 9007) powder coating. The front of the floodlight is clear polycarbonate (PC). Very easy to attach. 90 $^{\circ}$ tilt on one side is possible. When the bracket is attached to the other side, the tilt is 90 $^{\circ}$ to the other side. The set includes the necessary mounting bolts and wrench. Complete with integrated microwave sensor and 6500K LED. Microwave sensor maximum height 3,5m. Workplane 180°, 10m from sensor.

IP65 IK08 100,35 lm/W





Product code 6008100007
Floduct code 6008100007
50 W
51 W
165-240 V
≥0.90
50/60 Hz
6500 K
100,35 lm/W
5118 lm
≥80
<21,5
Flicker-Free
1200
170x135x65 mm
0,654 kg
Aluminum
Grey
Clear polycarbonate
-30+50°C
30000 h
SANAN
Integrated

Mounting information	
Mounting type	Surface
Mounting location	Wall or ceiling
Capabilities	
Dimmable	No
Type of connection	Wire 3x0,75
Standards and Certificates	
Protection class IK	IK08
Type of protection IP	IP65
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package

Product code	6008100007
Package	Carton box
Units in carton	1 pcs
Package diameters, weight bruto	198x152x50 mm , 0,654 kg
Product EAN code	4772007007905
Second package	
Package	Carton box
Units in second package	20 pcs
Package diameters, weight bruto	415x275x325 mm , 13,608 kg
ShipPing carton EAN code	4772007007929

ACCESSORIES

ENERGY EFFICIENCY



DIMENSIONS

135 mm



ALL FAMILY PRODUCTS

6008100006 BRENTSENS_30W_LED_3600 6008100007 BRENTSENS_50W_LED_6000

