

OSLO LED DOWNLIGHT

PRODUCT DATASHEET

OSLO100_B_10W_LED_1000

Surface LED spotlight with flood distribution.

360° rotatable. 90° tilt adjustable.

IP20. Body: Aluminium

powder coated black color.

Complete with 4000K LED



IP20

IK05

105,81 lm/W

TECHNICAL DATA

SKU:

6005000030

Electrical data

Nominal wattage	10 W
Operating wattage	9,46 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

Photometrical data

Color temperature (CCT)	4000 K
Luminous efficiency	105,81 lm/W
Luminous flux	1001 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

Light technical data

Beam angle	24°
------------	-----

Dimensions and weight

Diameter	Ø100 mm
Height	105 mm
Weight Neto	0,440 kg

Materials

Body material	Aluminium
Housing color	Black
Difuser material	Polycarbonate, UV-stabilised.

Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

Lifespan

Lifespan L80/B10 at 25°	50000 h
Led Brand	EPISTAR
Driver	DL-10W300-L

Mounting information

Mounting type	Surface
Mounting location	Ceiling/ Wall
Capabilities	
Dimmable	No
Type of connection	Wires 2-pole
Standards and Certificates	
Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package


Product code	6005000030
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	110x110x120 mm ; 0,488 kg
Product EAN code	4772007006144

Second package

Package	Carton box
Units in second package	24 pcs
Package diameters, weight bruto	450x235x375 mm ; 12,274 kg
ShipPing carton EAN code	4772007006939

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6005000030 OSLO100_B_10W_LED_1000
6005000031 OSLO100_B_15W_LED_1500
6005000028 OSLO100_W_10W_LED_1000
6005000029 OSLO100_W_15W_LED_1500



TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.