

PRODUCT DATASHEET

TANGA90_7W_W_3K_LED_630

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die- cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

96,59 lm/W

TECHNICAL DATA		Product code	6006000031
Electrical data			
Nominal wattage	7 W		
Operating wattage	6,522 W		
Nominal Voltage	165-240 V		
Power factor	≥0.50		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	3000 K		
Luminous efficiency	96,59 lm/W		
Luminous flux	630 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21,5		
Light technical data			
Beam angle	45°		
Dimensions and weight			
Dimensions	55x55x120 mm		
Weight Neto	0,250 kg		
Materials			
Body material	Aluminium		
Housing color	White		
Difuser material	Polycarbonate, UV-stabilised.		
Operating conditions			
Ambient temperature range	-20...+65°C		
Lifespan			
Lifespan L80/B10 at 25°	30000 h		
Led Brand	BRIDGELUX		
Driver	DL-7W300-L		
Mounting information			
Mounting type	Surfaced		
Mounting location	Ceiling		
Capabilities			
Dimmable	No		
Type of connection	Wires 2-pole		

Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package


Product code	6006000031
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	135x65x65 mm ; 0,272 kg
Product EAN code	4772007012725

Second package

Package	Carton
Units in second package	100 pcs
Package diameters, weight bruto	685x350x290 mm ; 27,976 kg
ShipPing carton EAN code	4772007013647

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6006000031	TANGA90_7W_W_3K_LED_630
6006000032	TANGA90_12W_W_3K_LED_1080
6006000033	TANGA90_15W_W_3K_LED_1350
6006000034	TANGA90_7W_B_3K_LED_630
6006000035	TANGA90_12W_B_3K_LED_1080
6006000036	TANGA90_15W_B_3K_LED_1350