

PRODUCT DATASHEET

TULSA90_15W_W_3K_LED_1350

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die-cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

96,49 lm/W

TECHNICAL DATA

SKU:

6006000026

Electrical data

Nominal wattage	15 W
Operating wattage	13,99 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

Photometrical data

Color temperature (CCT)	3000 K
Luminous efficiency	96,49 lm/W
Luminous flux	1350 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

Light technical data

Beam angle	45°
------------	-----

Dimensions and weight

Diameter	Ø95 mm
Height	140 mm
Weight Neto	0,474 kg

Materials

Body material	Aluminium
Housing color	White
Difuser material	Polycarbonate, UV-stabilised.

Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

Lifespan

Lifespan L80/B10 at 25°	30000 h
Led Brand	BRIDGELUX
Driver	DL-20W-L-01

Mounting information

Mounting type	Surfaced
Mounting location	Ceiling

Capabilities

Dimmable	No
Type of connection	Wires 2-pole

Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package


Product code	6006000026
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	150x100x100 mm ; 0,518 kg
Product EAN code	4772007012671

Second package

Package	Carton
Units in second package	30 pcs
Package diameters, weight bruto	520x325x320 mm ; 16,216 kg
ShipPing carton EAN code	4772007013593

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6006000025	TULSA90_10W_W_3K_LED_900
6006000026	TULSA90_15W_W_3K_LED_1350
6006000027	TULSA90_20W_W_3K_LED_1800
6006000028	TULSA90_10W_B_3K_LED_900
6006000029	TULSA90_15W_B_3K_LED_1350
6006000030	TULSA90_20W_B_3K_LED_1800