

MORA LED CEILING LIGHT SURFACE ROUND

PRODUCT DATASHEET
MORA95_SU_B_70W_LED_6650

A surfaced/suspended with mounting cables (max 1m long cables) , circular LED luminaire, with 100mm profile. The luminaire have the option of choosing a color temperature from 3000 to 6500K. Electronic, fixed output control gear. IP20. Body: steel, Black (RAL 9005). Diffuser: acrylic. Connection via push wire terminal blocks. Supplied with adjustable wire and cables, for suspended mounting. Complete with 3000 - 4000 - 6500K LED. There is option to change CCT by dip switch.



IP20

IK05

109,50 lm/W

TECHNICAL DATA

SKU: 6004000034

Electrical data

| | |
|-------------------|-----------|
| Nominal wattage | 70 W |
| Operating wattage | 79,44 W |
| Nominal Voltage | 220-240 V |
| Power factor | ≥0.90 |
| Mains frequency | 50/60 Hz |

Photometrical data

| | |
|-----------------------------|-------------|
| Color temperature (CCT) | 3000-6500 K |
| Luminous efficacy | 109,50 lm/W |
| Luminous flux | 8699 lm |
| Color rendering index (CRI) | ≥80 |
| Unified Glare Rating (UGR) | <21,5 |

Light technical data

| | |
|------------|------|
| Beam angle | 120° |
|------------|------|

Dimensions and weight

| | |
|-------------|----------|
| Diameter | Ø800 mm |
| Height | 100 mm |
| Weight Neto | 7,430 kg |

Materials

| | |
|------------------|----------|
| Body material | Aluminum |
| Housing color | Black |
| Difuser material | Acrylic |

Operating conditions

| | |
|---------------------------|-------------|
| Ambient temperature range | -20...+65°C |
|---------------------------|-------------|

Lifespan

| | |
|-------------------------|---------------------|
| Lifespan L70/B10 at 25° | 50000 h |
| Led Brand | BRIDGELUX |
| Driver | LF-GIF040YA(H)1050H |

Mounting information

| | |
|-------------------|----------------------|
| Mounting type | Surfaced / Suspended |
| Mounting location | Ceiling |


| | |
|----------------------------|-------------------------------|
| Capabilities | |
| Dimmable | No |
| Type of connection | Via push wire terminal blocks |
| Standards and Certificates | |
| Protection class IK | IK05 |
| Type of protection IP | IP20 |
| Standards | CE, RoHS |
| Warranty | 36 months |

LOGISTICAL DATA

| | |
|---------------------------------|---------------------------|
| Main package | |
| Product code | 6004000034 |
| Package | Carton box |
| Units in carton | 1 pcs |
| Package diameters, weight bruto | 855x840x170 mm; 10,070 kg |
| Product EAN code | 4772007005352 |

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

- 6004000029 MORA95_SU_W_40W_LED_3800
- 6004000030 MORA95_SU_W_60W_LED_5700
- 6004000031 MORA95_SU_W_70W_LED_6650
- 6004000032 MORA95_SU_B_40W_LED_3800
- 6004000033 MORA95_SU_B_60W_LED_5700
- 6004000034 MORA95_SU_B_70W_LED_6650

- 6004100029 MORA95_SU_W_40W_LED_3800_0-10V
- 6004100031 MORA95_SU_W_70W_LED_6650_0-10V
- 6004100032 MORA95_SU_B_40W_LED_3800_0-10V
- 6004100034 MORA95_SU_B_70W_LED_6650_0-10V

