

PRODUCT DATASHEET LION100_18W_LED_2520

Dust and water resistant LED luminaire, IP65, IK08, Electronic, fixed output control gear. Housing: white Polycarbonate (PC). Diffuser: Polycarbonate (PC) . For surface or suspended mounting Supplied with quick-fix brackets, for surface mounting. Complete with 4000K LED. The luminaire could be connected to the line, quick connection.





IP65	IK08	140 lm/W
------	------	----------

TECHNICAL DATA		Product code	6007000025
Electrical data			
Nominal wattage	18W		
Nominal Voltage	165-240 V		
Power factor	≥0.90		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	4000 K		
Luminous efficiency	140 lm/W		
Luminous flux	2520 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21,5		
Flicker index	Flicker-Free		
Light technical data			
Beam angle	120°		
Dimensions and weight			
Dimension	600x70x50 mm		
Weight Neto	0,347 kg		
Materials			
Body material	Polycarbonate (PC)		
Housing color	White		
Difuser material	Polycarbonate (PC)		
Operating conditions			
Ambient temperature range	-20+65°C		
Lifespan			
Lifespan L90/B10 at 25°	50000 h		
Led Brand	EPISTAR		
Driver	2x CE_ Relux		
Mounting information			
Mounting type	Surfaced / Suspended	Surfaced / Suspended	
Mounting location	Ceiling / Wall		


Capabilities		
Dimmable	-	
Type of connection	Via push wire terminal blocks	
Max power in the line	to 200W	
Standards and Certificates		
Protection class IK	IK08	
Type of protection IP	IP65	
Standards	CE, RoHS	
Warranty	60 months	

LOGISTICAL DATA


Main package

Product code	6007000025	
Package	Paper and plastic	
Units in carton	1 pcs	
Package diameters, weight bruto	611x73x53mm; 0,358kg	
Product EAN code	4772007015009	
Second package		
Package	Carton box	
Units in second package	12 pcs	
Package diameters, weight bruto	645x240x240mm; 4,852kg	
ShipPing carton EAN code	4772007015016	


ENERGY EFFICIENCY








DIMENSIONS





ALL FAMILY PRODUCTS

6007000025 LION140_18W_LED_2520 6007000026 LION140_36W_LED_5040 6007000027 LION140_50W_LED_7000 6007000028 LION140_70W_LED_9800



Polar LDC