

## PRODUCT DATASHEET

### SOPOT\_2x24W\_R\_LED\_4470

Surfaced round LED luminaire. Electronic, Infrared wireless dimmable and CCT adjustable output control gear. Body white painted steel.  
Diffuser: Polycarbonate (PC).  
IP20. 3000 to 6500K CCT adjustable.  
Remote included to the set.



IP20

IK05

97,02 lm/W

#### TECHNICAL DATA

SKU: 6004000056

##### Electrical data

Nominal wattage	2x24 W
Operating wattage	46,01 W
Nominal Voltage	165-240 V
Power factor	≥0.90
Mains frequency	50/60 Hz

##### Photometrical data

Color temperature (CCT)	3000 to 6500 K
Luminous efficacy	97,02 lm/W
Luminous flux	4464 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21.5
Flicker index	Flicker-Free

##### Light technical data

Beam angle	120°
------------	------

##### Dimensions and weight

Diameter	Ø380 mm
Height	70 mm
Weight Neto	0,812kg

##### Materials

Body material	Steel
Housing color	White
Difuser material	Polycarbonate (PC)

##### Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

##### Lifespan

Lifespan L70/B50 at 25°	30000 h
Led Brand	EPISTAR
Driver	TOPE (8-24W*2(MAX))

##### Mounting information

Mounting type	Surface
Mounting location	Ceiling


Capabilities	
Dimmable	Yes
Type of connection	Via wires terminal blocks
Standards and Certificates	
Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

## LOGISTICAL DATA


Main package	
Product code	6004000056
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	440x440x80mm ; 1,128 kg
Product EAN code	4772007006793
Second package	
Package	Carton box
Folding carton boxes in shipping carton	10 pcs
Package diameters, weight bruto	900x425x460mm ; 12,578 kg
Shipping carton EAN code	4772007006830

## ACCESSORIES

## ENERGY EFFICIENCY



## PHOTOMETRIC DIAGRAM



## ALL FAMILY PRODUCTS

6004000055	SOPOT_2x18W_R_LED_3320
6004000056	SOPOT_2x24W_R_LED_4470
6004000057	SOPOT_2x36W_R_LED_6740
6004000058	SOPOT_2x48W_R_LED_9030

